## ACCESZIBI-LITY IN PUBLIC & COMMERCIAL BUILDINGS

## Aritco PublicLift Access Datasheet 2025

Aritco PublicLift Access is designed to make public and commercial buildings accessible for everyone. The lift expresses Scandinavian design and features a backlit panel and lit handlebar.

Advantages offered by Aritco PublicLift Access:

- Design, sizes and options tailored for public environments
- 95% recyclable materials
- Patented screw and nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Equipped with our SmartSafety system with safety features for public environments

For more information please visit **aritco.com** 











**Aritco Lift AB** Elektronikhöjden 14, Box 516 175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00 E: info@aritco.com www.aritco.com

## Explore Aritco PublicLift Access

## Key features

Alternative models OUTDOOR version GOODS version Aritco PublicLift Access comes with customization possibilities. Choose from more than 200 different colours, 2 different glass types and 8 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in several different sizes, and on the larger ones you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is SmartLift enabled which means that a maintenance provider can get access to a Fleet management system for remote monitoring and support of the lift. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to prevent accidents.



Sizes					
MOL				WHEELCHAIR	
<b>1</b>		1300 x 1160 mm	250 kg / 2 persons	-	
2		1300 x 1400 mm	410 kg / 5 persons	Lone user or type A*	
3		1300 x 1600 mm	410, 500 kg / 5, 6 pers.	A or B with attendent*	
	1000 / 1200 // 1111	1400 x 1400 mm	410 kg / 5 persons	Lone user or type A*	
5		1400 x 1600 mm	410, 500 kg / 5, 6 pers.	A or B with attendent*	
6	1100 x 1480 mm	1500 x 1600 mm	410, 500 kg / 5, 6 pers. A	or B with attendent, adjacent entry*	
7	1000 x 1980 mm	1400 x 2100 mm	500 kg / 6 persons	A or B with attendent*	
8	1100 x 1580 mm	1500 x 1700 mm	500 kg / 6 persons		
* Natio	nal guidelines may apply. Wheel	chair Type A and B according to EN	12183/EN 12184.		
Lift color	from the RAL K7 cla	Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colours)			
<b>Glass</b> 2 different glass types to choose from.	STANDARD Clear glass	B OPTIONAL Tinted glass			
<b>Floor</b> 8 different floorings.	By crest	Alled of the pass	to the stud of the stude of the		
Installation environment	: Indoor	Type of lift	Platform lift intended for ir commercial environments.		
Drive system	Patented screw-and	Patented screw-and-nut system			
Motor	2.8 kW motor	Rated speed	Max 0,15 m/s inside Europ Max 0.25 m/s outside Euro		
Technical compliance		European Machine directive 2006/42/EC European standard EN 81-41			
Emergency lowering	Battery-powered.	Battery-powered.			
Travel height	500 - 13 000 mm	Top height	Min. 2 240		
Number of floors	2 to 6 floors	2 to 6 floors			
Installation		Recessed installation 50 mm below floor Installed directly on the floor with 50 mm ramp			
Operation		Hold to run – press and hold For installations outside Europe – One touch operation (press one time)			
Power supply	230 V 1-phase 400 V 3-phase				
Warranty		Aritco PublicLift Access comes with a 5-year product warranty and a 10-year drive technology warranty.			
Alternative model	intended for both pe Aritco PublicLift Acc with corrosion class	Aritco PublicLift Access GOODS version is a version of the Aritco PublicLift Access lift that is intended for both persons and goods. Aritco PublicLift Access OUTDOOR version is designed for outdoor use. All outdoor lifts are delivered with corrosion class C5 guides to avoid corrosion. For more information please visit aritco.com			